

170-03063

Article Number: 170-03063

Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver 100.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03063

Type BSHTTST34SR

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
 - Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver 100.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Max. (Imperial) 0.687 "

Bundle Diameter Max. (Metric) 17.5 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

Logistics and Packaging

Package Quantity 100 ft

Package Quantity (Metric) 1 Reel

Weight (Metric) 1.57 kg

Weight (imperial) 3.45 lbs

Material and Specifications

Material Aluminium (AL)
Glass Fiber (GF)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes

