

170-03071

Article Number: 170-03071

Flame Retardant Expandable Braided Sleeving, 0.13" Dia., Gray, 225.0 ft/Standard Reel



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03071

**Type** BSPFR188

**Color** Gray (GY)

**Features and Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description** Flame Retardant Expandable Braided Sleeving, 0.13" Dia., Gray, 225.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 225.0 ft

**Length L (Metric)** 68.6 m

**Reel Length (imperial)** 225.0 ft

**Bundle Diameter Min. (Imperial)** 0.094 "

**Bundle Diameter Min. (Metric)** 2.4 mm

**Bundle Diameter Max. (Imperial)** 0.25 "

**Bundle Diameter Max. (Metric)** 6.4 mm

**Nominal Diameter (Imperial)** 1/8 "

**Nominal Diameter (Metric)** 3.2 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 225 ft

**Package Quantity (Metric)** 225.0 ft

**Weight (Metric)** 0.18 kg

**Weight (imperial)** 0.4 lbs

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** FMVSS 302  
FAR 25

VW-1  
Mil-202

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes