

170-03094



Article Number: 170-03094

Flame Retardant Expandable Braided Sleeving, 1.25" Dia., Black, 250.0 ft/Bulk Reel



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03094

**Type** BSPFR1140B

**Color** Black (BK)

**Features and Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description** Flame Retardant Expandable Braided Sleeving, 1.25" Dia., Black, 250.0 ft/Bulk Reel

## Product Dimensions

**Length L (Imperial)** 250.0 ft

**Length L (Metric)** 76.2 m

**Reel Length (imperial)** 250.0 ft

**Bundle Diameter Min. (Imperial)** 0.75 "

**Bundle Diameter Min. (Metric)** 19.1 mm

**Bundle Diameter Max. (Imperial)** 1.75 "

**Bundle Diameter Max. (Metric)** 44.5 mm

**Nominal Diameter (Imperial)** 1-1/4 "

**Nominal Diameter (Metric)** 31.8 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 250 ft

**Package Quantity (Metric)** 250.0 ft

**Weight (Metric)** 1.8 kg

**Weight (imperial)** 4.0 lbs

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** Mil-202  
VW-1

FAR 25  
FMVSS 302

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**Certification/Specification** UL94

**UL Recognized (US and Canada)** Yes