

170-03097

Article Number: 170-03097

Aluminum Laminated Fiberglass Sleeving, 2.5" Dia., Silver, 50.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

## Base Data

**Local Order Number** 170-03097

**Type** BSHTTST212SR

**Color** Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
  - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
  - Cuts with ordinary scissors for fast, easy application.

**Product Description** A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

**Short Description** Aluminum Laminated Fiberglass Sleeving, 2.5" Dia., Silver, 50.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 50.0 ft

**Length L (Metric)** 15.2 m

**Reel Length (imperial)** 50.0 ft

**Bundle Diameter Max. (Imperial)** 2.375 "

**Bundle Diameter Max. (Metric)** 60.3 mm

**Nominal Diameter (Imperial)** 2-1/2 "

**Nominal Diameter (Metric)** 63.5 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 50 ft

**Package Quantity (Metric)** 1

**Weight (Metric)** 2.3 kg

**Weight (imperial)** 5.05 lbs

## Material and Specifications

**Material** Aluminium (AL)  
Glass Fiber (GF)

**Flammability** non flammable

**Operating Temperature** -76°F to +491°F (-60°C to +255°C)

**ROHS Compliant** Yes

