

170-03099



Article Number: 170-03099

Plenum Rated Expandable Braided Sleeving (Halar), 0.13" Dia., White, 225.0 ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03099

Type BSHLR1810

Color White (WH)

Features and Benefits

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Product Description Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.

Short Description Plenum Rated Expandable Braided Sleeving (Halar), 0.13" Dia., White, 225.0 ft/Reel

Product Dimensions

Length L (Imperial) 225.0 ft

Length L (Metric) 68.6 m

Reel Length (imperial) 225.0 ft

Width W (Imperial) 0.01 "

Width W (Metric) .25 mm

Bundle Diameter Min. (Imperial) 0.094 "

Bundle Diameter Min. (Metric) 2.4 mm

Bundle Diameter Max. (Imperial) 0.25 "

Bundle Diameter Max. (Metric) 6.4 mm

Nominal Diameter (Imperial) 1/8 "

Nominal Diameter (Metric) 3.1 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 225 ft

Weight (imperial) 0.56 lbs

Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1
FAR 25

Operating Temperature -103°F to +302°F (-75°C to +150°C)

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes