HellermannTyton

170-03107

	Article Number: 170-03107 Plenum Rated Expandable Braided Sleeving (Halar), 0.75" Dia., White, 75.0 ft/Reel
Download drawing	nload spec sheet
Base Data	

Local Order Number	170-03107
Туре	BSHLR3410
Color	White (WH)
Features and Benefits	 Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications. Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation. Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 0.75" Dia., White, 75.0 ft/Reel

Product Dimensions

Length L (Imperial)	75.0 ft
Length L (Metric)	22.9 m
Reel Length (imperial)	75.0 ft
Bundle Diameter Min. (Imperial)	0.5 "
Bundle Diameter Min. (Metric)	12.7 mm
Bundle Diameter Max. (Imperial)	1.25 "
Bundle Diameter Max. (Metric)	31.8 mm
Nominal Diameter (Imperial)	3/4 "
Nominal Diameter (Metric)	19.1 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	75 ft
Weight (imperial)	1.28 lbs
Weight (Metric)	0.58 kg

Material and Specifications

Material	Polyamide 6.6 (E/CTFE)
Material Shortcut	E/TFE
Flammability	UL VW-1 FAR 25
Operating Temperature	-103°F to +302°F (-75°C to +150°C)

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes

© HellermannTyton 2015