# HellermannTyton

## 170-03128

	Article Number: 170-03128 Split Wrap Braided Sleeving, 1.0" ID, PET, Black, 100.0 ft/Bulk Reel	
Download drawing Download spec sheet		
Base Data		
Local Order Nun	nber 170-03128	

Type Color	BSPSW100B Black (BK)
Features and Benefits	<ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul>
Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Short Description	Split Wrap Braided Sleeving, 1.0" ID, PET, Black, 100.0 ft/Bulk Reel

#### **Product Dimensions**

Length L (Imperial)	100.0 ft
Length L (Metric)	30.48 m
Reel Length (imperial)	100.0 ft
Bundle Diameter Max. (Imperial)	1.0 "
Bundle Diameter Max. (Metric)	25.4 mm
Nominal Diameter (Imperial)	1 "
Nominal Diameter (Metric)	25.4 mm

### Logistics and Packaging

Quantity Per	box
Package Quantity	100 ft
Weight (imperial)	2.0 lbs
Weight (Metric)	0.91 kg

#### **Material and Specifications**

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL94 V0
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
<b>ROHS</b> Compliant	Yes
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015