# HellermannTyton

# 170-03139

	Article Number: 170-03139 Split Wrap Braided Sleeving, 2.0" ID, PET, Black, 150.0 ft/Large Bulk Reel
Download drawing	wnload spec sheet
Base Data	
Local Order Nu	mber 170-03139
	Type BSPSW2001 B

Туре	BSPSW200LB
Color	Black (BK)
Features and Benefits	<ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul>
Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling
	requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Short Description	Split Wrap Braided Sleeving, 2.0" ID, PET, Black, 150.0 ft/Large Bulk Reel

#### **Product Dimensions**

Length L (Imperial)	150.0 ft
Length L (Metric)	45.72 m
Reel Length (imperial)	150.0 ft
Bundle Diameter Max. (Imperial)	2.0 "
Bundle Diameter Max. (Metric)	50.8 mm
Nominal Diameter (Imperial)	2"
Nominal Diameter (Metric)	50.8 mm

## Logistics and Packaging

Quantity Per	box
Package Quantity	150 ft
Weight (Metric)	2.4 kg
Weight (imperial)	5.4 lbs

### Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL94 V0
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
<b>ROHS</b> Compliant	Yes
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015