HellermannTyton

181-00170 Article Number: 181-00170 Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Gray, 30ft/Box RoHS Download drawing Download spec sheet **Base Data** Local Order Number 181-00170 Type SD1X1 Color Gray (GY) Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. . Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. · Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately) Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths. Short Description Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	1.0 "
Width W (Metric)	25.4 mm
Width W2 (Imperial)	1.0 "
Width W2 (Metric)	25.4 mm
Height H (Imperial)	1.06 "
Height H (Metric)	26.9 mm
Mounting Hole Centers (Imperial)	4.0 "

Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)
Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015