HellermannTyton

181-00174 Article Number: 181-00174 Solid Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, Gray, 30ft/Box RoHS HellermannTyton Download spec sheet **Base Data** Local Order Number 181-00174 Type SD1X3 Color Gray (GY) Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. . Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. · Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately) Product Description HellemannTyton's Pro-Duct solid wall wiring duct efficiently routes and protects wires and cables. Solid wall wiring duct is designed for straight wire runs where breakouts are not required. Pro-Duct solid wall wiring duct is manufactured from high-impact, rigid PVC, and is available in 6-foot lengths in standard colors of white, gray and black. Short Description Solid Wall Wiring Duct, 1" X3", Non-Adhesive, PVC, Gray, 30ft/Box **Product Dimensions** Length L (Imperial) 6.0 ft Length L (Metric) 1.83 m Width W (Imperial) 1.0 " Width W (Metric) 25.4 mm

Width W2 (Imperial)	1.0 "
Width W2 (Metric)	25.4 mm
Height H (Imperial)	3.07 "
Height H (Metric)	77.9 mm
Mounting Hole Centers (Imperial)	4.0 "

Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)
Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015