

181-00231

Article Number: 181-00231

High Density Slotted Wall Wiring Duct, 2.5" X 3", Adhesive, PVC, Gray, 30ft/Carton

HellermannTyton



Download spec sheet

Base Data

Local Order Number 181-00231

Type SLHDA2.5X3

Color Gray (GY)

Features and Benefits

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 2.5" X 3", Adhesive, PVC, Gray, 30ft/Carton

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 2.5 "

Width W (Metric) 63.5 mm

Width W2 (Imperial) 2.5 "

Width W2 (Metric) 63.5 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 2.6 "

Width W5 (metric) 66.0 mm

Width W6 (imperial) 0.75 "

Width W6 (metric) 19.05 mm

Height H (Imperial) 3.07 "

Height H (Metric) 77.9 mm

Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA
UL

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No