

181-00233

Article Number: 181-00233

High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, White, 30ft/Box

HellermannTyton



Download spec sheet

Base Data

Local Order Number 181-00233
Type SLHD2.5X3
Color White (WH)

Features and Benefits

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft
Length L (Metric) 1.83 m
Width W (Imperial) 2.5 "
Width W (Metric) 63.5 mm
Width W2 (Imperial) 2.5 "
Width W2 (Metric) 63.5 mm
Width W3 (Imperial) 0.16 "
Width W3 (Metric) 4.1 mm
Width W4 (imperial) 0.4 "
Width W4 (metric) 10.2 mm
Width W5 (imperial) 2.6 "
Width W5 (metric) 66.0 mm
Width W6 (imperial) 0.75 "
Width W6 (metric) 19.05 mm
Height H (Imperial) 3.07 "
Height H (Metric) 77.9 mm
Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per box
Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA
UL

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No