

181-00245



Article Number: 181-00245

Solid Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, Gray, 30ft/Box



Download drawing



Download spec sheet

Base Data

Local Order Number 181-00245

Type SD2X5

Color Gray (GY)

Features and Benefits

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

Short Description Solid Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Width W2 (Imperial) 2.0 "

Width W2 (Metric) 50.8 mm

Width W6 (imperial) 0.5 "

Width W6 (metric) 12.7 mm

Height H (Imperial) 5.07 "

Height H (Metric) 128.8 mm

Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 30.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No