

181-00253

Article Number: 181-00253

High Density Slotted Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, Gray, 30ft/Box

HellermannTyton



Download spec sheet

## Base Data

**Local Order Number** 181-00253  
**Type** SLHD2X5  
**Color** Gray (GY)

**Features and Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, Gray, 30ft/Box

## Product Dimensions

**Length L (Imperial)** 6.0 ft  
**Length L (Metric)** 1.83 m  
**Width W (Imperial)** 2.0 "  
**Width W (Metric)** 50.8 mm  
**Width W2 (Imperial)** 2.0 "  
**Width W2 (Metric)** 50.8 mm  
**Width W3 (Imperial)** 0.16 "  
**Width W3 (Metric)** 4.1 mm  
**Width W4 (imperial)** 0.4 "  
**Width W4 (metric)** 10.2 mm  
**Width W5 (imperial)** 4.6 "  
**Width W5 (metric)** 116.8 mm  
**Width W6 (imperial)** 0.5 "  
**Width W6 (metric)** 12.7 mm  
**Height H (Imperial)** 5.07 "  
**Height H (Metric)** 128.8 mm  
**Mounting Hole Centers (Imperial)** 2.0 "

## Logistics and Packaging

**Quantity Per** box  
**Package Quantity** 30.0 ft

**Package Quantity (Metric)** 9.1 m

**Carton Quantity** 120.0 ft

## Material and Specifications

---

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** CSA  
UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No

**UL Recognized (US)** Yes