HellermannTyton


181-15102



Article Number: 181-15102

Solid Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, White, 120ft/Carton

RoHS



Base Data

Local Order Number	181-15102
Туре	SD1.5X1
Color	White (WH)
Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
	 Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately
Product Description	HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	1.5 "
Width W (Metric)	38.1 mm
Width W2 (Imperial)	1.5 "
Width W2 (Metric)	38.1 mm
Height H (Imperial)	1.06 "
Height H (Metric)	26.9 mm
Mounting Hole Centers (Imperial)	4.0 "

Logistics and Packaging

Quantity Per	carton
Package Quantity	120.0 ft
Package Quantity (Metric)	36.6 m
Carton Quantity	120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)

ROHS Compliant Yes

Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes

UL Recognized (US and Canada) No

© HellermannTyton 2015