

181-15503



Article Number: 181-15503

Solid Wall Wiring Duct, 1.5" X 1.5", Non-Adhesive, PVC, White, 120ft/Carton



Download drawing



Download spec sheet

Base Data

Local Order Number 181-15503

Type SD1.5X1.5

Color White (WH)

Features and Benefits

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

Short Description Solid Wall Wiring Duct, 1.5" X 1.5", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.5 "

Width W (Metric) 38.1 mm

Width W2 (Imperial) 1.5 "

Width W2 (Metric) 38.1 mm

Height H (Imperial) 1.57 "

Height H (Metric) 39.9 mm

Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per carton

Package Quantity 120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA
UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes