# HellermannTyton

## 181-15513

101-13313		
Art	ticle Number: 181-15513	
Slo	otted Wall Wiring Duct, 1.5" X 1.5", Adhesive, PVC, Gray, 120ft/Carton	
A CONTRACTOR	¢ RoHS	
Download drawing	spec sheet	
Base Data		
Local Order Number	181-15513	
Туре	SLA1.5X1.5	
Color	Gray (GY)	
Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> </ul>	

• Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

**Product Description** Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".

Short Description Slotted Wall Wiring Duct, 1.5" X 1.5", Adhesive, PVC, Gray, 120ft/Carton

### **Product Dimensions**

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	1.5 "
Width W (Metric)	38.1 mm
Width W2 (Imperial)	1.5 "
Width W2 (Metric)	38.1 mm
Width W3 (Imperial)	0.4 "
Width W3 (Metric)	10.2 mm
Width W4 (imperial)	1.0 "
Width W4 (metric)	25.4 mm
Width W5 (imperial)	1.2 "
Width W5 (metric)	30.5 mm
Height H (Imperial)	1.57 "
Height H (Metric)	39.9 mm
Mounting Hole Centers (Imperial)	4.0 "

#### **Logistics and Packaging**

Quantity Per	carton
Package Quantity	120.0 ft
Package Quantity (Metric)	36.6 m
Carton Quantity	120.0 ft

## Material and Specifications

Material	PolyvinyIchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015