

181-15514

Article Number: 181-15514

Slotted Wall Wiring Duct, 1.5" X 1.5", Adhesive, PVC, White, 30ft/Box

HellermannTyton



Download spec sheet

Base Data

Local Order Number 181-15514
Type SLA1.5X1.5
Color White (WH)

Features and Benefits

- Strong fingers prevent unwanted breaking.
- Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

Product Description Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".

Short Description Slotted Wall Wiring Duct, 1.5" X 1.5", Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft
Length L (Metric) 1.83 m
Width W (Imperial) 1.5 "
Width W (Metric) 38.1 mm
Width W2 (Imperial) 1.5 "
Width W2 (Metric) 38.1 mm
Width W3 (Imperial) 0.4 "
Width W3 (Metric) 10.2 mm
Width W4 (imperial) 1.0 "
Width W4 (metric) 25.4 mm
Width W5 (imperial) 1.2 "
Width W5 (metric) 30.5 mm
Height H (Imperial) 1.57 "
Height H (Metric) 39.9 mm
Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per box
Package Quantity 30.0 ft
Package Quantity (Metric) 9.1 m
Carton Quantity 120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes