# HellermannTyton

#### 181-21007



Article Number: 181-21007

Slotted Wall Wiring Duct, 2" X 1", Non-Adhesive, PVC, White, 120ft/Carton





#### **Base Data**

Local Order Number 181-21007

> SL2X1 Type

Color White (WH)

- Features and Benefits Strong fingers prevent unwanted breaking.
  - Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.
  - · Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without

disconnection.

Product Description Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider

opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".

Short Description Slotted Wall Wiring Duct, 2" X1", Non-Adhesive, PVC, White, 120ft/Carton

### **Product Dimensions**

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Width W2 (Imperial) 2.0 "

Width W2 (Metric) 50.8 mm

Width W3 (Imperial) 0.4 "

Width W3 (Metric) 10.2 mm

Width W4 (imperial) 1.0 "

Width W4 (metric) 25.4 mm

Width W5 (imperial) 0.75 "

Width W5 (metric) 19.1 mm

Width W6 (imperial) 0.5 "

Width W6 (metric) 12.7 mm

Height H (Imperial) 1.06 "

Height H (Metric) 26.9 mm

Mounting Hole Centers (Imperial) 4.0 "

#### **Logistics and Packaging**

Quantity Per carton

Package Quantity 120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

## **Material and Specifications**

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No