

181-75750

Article Number: 181-75750

Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, Gray, 30ft/Box

HellermannTyton



Download drawing



Download spec sheet

## Base Data

Local Order Number 181-75750

Type SD.75X.75

Color Gray (GY)

- Features and Benefits**
- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
  - Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
  - Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, .75" X .75", Non-Adhesive, PVC, Gray, 30ft/Box

## Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 0.75 "

Width W (Metric) 19.1 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Height H (Imperial) 0.8 "

Height H (Metric) 20.3 mm

Mounting Hole Centers (Imperial) 4.0 "

## Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

## Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** CSA  
UL

**UL Listed (US and Canada)** No

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** No