HellermannTyton

181-75752	
	ticle Number: 181-75752 Did Wall Wiring Duct, .75'' X .75'', Adhesive, PVC, Gray, 30ft/Box
HellermannTyton	
Download spec sheet	
Base Data	
Local Order Number	181-75752
Туре	SDA.75X.75
Color	Gray (GY)
Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placemen Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, .75" X .75", Adhesive, PVC, Gray, 30ft/Box
Product Dimensions	
Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	0.75 "
Width W (Metric)	19.1 mm

Width W2 (Imperial)1.0 "Width W2 (Metric)25.4 mmHeight H (Imperial)0.8 "Height H (Metric)20.3 mm

Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)
Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015