HellermannTyton

184-11004



Article Number: 184-11004

High Density Slotted Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, Gray, 120ft/Carton







Base Data

Local Order Number 184-11004

Type SLHD1X1

Color Gray (GY)

- Features and Benefits Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
 - · Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier

installation.

• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to

accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted

wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" X1", Non-Adhesive, PVC, Gray, 120ft/Carton

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 0.75 "

Width W5 (metric) 19.05 mm

Height H (Imperial) 1.06 "

Height H (Metric) 26.9 mm

Mounting Hole Centers (Imperial)

Logistics and Packaging

Quantity Per carton

Package Quantity 120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No