

184-11012



Article Number: 184-11012

High Density Slotted Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, White, 120ft/Carton



Download drawing



Download spec sheet

Base Data

Local Order Number 184-11012
Type SLHD1X1.5
Color White (WH)

Features and Benefits

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (Imperial) 6.0 ft
Length L (Metric) 1.83 m
Width W (Imperial) 1.0 "
Width W (Metric) 25.4 mm
Width W2 (Imperial) 1.0 "
Width W2 (Metric) 25.4 mm
Width W3 (Imperial) 0.16 "
Width W3 (Metric) 4.1 mm
Width W4 (imperial) 0.4 "
Width W4 (metric) 10.2 mm
Width W5 (imperial) 1.19 "
Width W5 (metric) 30.2 mm
Height H (Imperial) 1.57 "
Height H (Metric) 39.9 mm
Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per carton
Package Quantity 120.0 ft
Package Quantity (Metric) 36.6 m
Carton Quantity 120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes