# HellermannTyton

## 184-12007

| His                   | ticle Number: 184-12007<br>gh Density Slotted Wall Wiring Duct, 1" X 2", Non-Adhesive, PVC, White, 120ft/Carton        |
|-----------------------|--|
| Download drawing      | spec sheet   |
| Base Data             |  |
| Local Order Number    | 184-12007  |
| Туре                  | SLHD1X2  |
| Color                 | White (WH)   |
| Features and Benefits | <ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li> </ul> |

| Features and Benefits | <ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li> <li>Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li> <li>Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommendate compared to compare installation.</li> </ul> |
|-----------------------|---|
| Product Description   | accommodate compact designs and ease installation.<br>Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.   |
| Short Description     | High Density Slotted Wall Wiring Duct, 1" X2", Non-Adhesive, PVC, White, 120ft/Carton   |

#### **Product Dimensions**

| Length L (Imperial)              | 6.0 ft  |
|----------------------------------|---------|
| Length L (Metric)                | 1.83 m  |
| Width W (Imperial)               | 1.0 "   |
| Width W (Metric)                 | 25.4 mm |
| Width W2 (Imperial)              | 1.0 "   |
| Width W2 (Metric)                | 25.4 mm |
| Width W3 (Imperial)              | 0.16 "  |
| Width W3 (Metric)                | 4.1 mm  |
| Width W4 (imperial)              | 0.4 "   |
| Width W4 (metric)                | 10.2 mm |
| Width W5 (imperial)              | 1.62 "  |
| Width W5 (metric)                | 41.1 mm |
| Height H (Imperial)              | 2.07 "  |
| Height H (Metric)                | 52.6 mm |
| Mounting Hole Centers (Imperial) | 2.0 "   |
|                                  |         |

#### **Logistics and Packaging**

| Quantity Per              | carton   |
|---------------------------|----------|
| Package Quantity          | 120.0 ft |
| Package Quantity (Metric) | 36.6 m   |
| Carton Quantity           | 120.0 ft |

### Material and Specifications

| Material                      | Polyvinylchloride (PVC) |
|-------------------------------|-------------------------|
| Material Shortcut             | PVC                     |
| Flammability                  | self-extinguishing      |
| Operating Temperature         | +122°F (+50°C)          |
| ROHS Compliant                | Yes                     |
| Certification/Specification   | UL<br>CSA               |
| UL Listed (US and Canada)     | No                      |
| UL Recognized (US and Canada) | No                      |
| UL Recognized (US)            | Yes                     |
|                               |                         |

© HellermannTyton 2015