

184-13007



Article Number: 184-13007

High Density Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 120ft/Carton



Download drawing



Download spec sheet

Base Data

Local Order Number 184-13007

Type SLHD1X3

Color White (WH)

- Features and Benefits**
- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
 - Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
 - Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 2.6 "

Width W5 (metric) 66.0 mm

Height H (Imperial) 3.07 "

Height H (Metric) 77.9 mm

Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per carton

Package Quantity 120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes