

184-44003

Article Number: 184-44003

High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, White, 30ft/Box

HellermannTyton



Download spec sheet

## Base Data

Local Order Number 184-44003

Type SLHD4X4

Color White (WH)

**Features and Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, White, 30ft/Box

## Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 4.0 "

Width W (Metric) 101.6 mm

Width W2 (Imperial) 4.0 "

Width W2 (Metric) 101.6 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 3.6 "

Width W5 (metric) 91.4 mm

Width W6 (imperial) 1.5 "

Width W6 (metric) 38.1 mm

Height H (Imperial) 4.07 "

Height H (Metric) 103.4 mm

Mounting Hole Centers (Imperial) 2.0 "

## Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

**Package Quantity (Metric)** 9.1 m

**Carton Quantity** 120.0 ft

## Material and Specifications

---

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** UL  
CSA

**UL Listed (US and Canada)** No

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** No