

## 1NFP0C



**Article Number:** 161-05004

**Spiralwrap, 1/8" Diameter, PE, Black, 100ft/RL**



Download spec sheet

### Base Data

<b>Local Order Number</b>	1NFP0C
<b>Type</b>	1NFP
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Sheathing allows flexible routing and lead-out of cables</li> <li>• The inner edges are beveled preventing damage to cables</li> <li>• Sheathing is reusable and resistant to most chemicals</li> <li>• Spiralwrap is U.L. Recognized</li> </ul>
<b>Product Description</b>	HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.
<b>Short Description</b>	Spiralwrap, 1/8" Diameter, PE, Black, 100ft/RL

### Product Dimensions

<b>Length L (Imperial)</b>	100.0 ft
<b>Length L (Metric)</b>	30.48 m
<b>Reel Length (imperial)</b>	100.0 ft
<b>Variant</b>	Spiral Binding
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.6 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.05 "
<b>Bundle Diameter Max. (Metric)</b>	12.7 mm
<b>Diameter D (imperial)</b>	0.125 "
<b>Diameter D (metric)</b>	3.18 mm
<b>Nominal Diameter (Imperial)</b>	1/8 "
<b>Nominal Diameter (Metric)</b>	3.18 mm
<b>Wall Thickness WT (Imperial)</b>	0.032 "
<b>Wall Thickness WT (Metric)</b>	0.81 mm
<b>Pitch (imperial)</b>	0.187 "
<b>Pitch (metric)</b>	4.75 mm

### Logistics and Packaging

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	100.0 ft
<b>Package Quantity (Metric)</b>	30.48 m
<b>Carton Quantity</b>	100.0 ft

## Material and Specifications

---

<b>Material</b>	Polyethylene (PE)
<b>Material Shortcut</b>	PE
<b>Flammability</b>	Flammable
<b>Operating Temperature</b>	-76°F to +190°F (-60°C to +88°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes