

1P9C



Article Number: 161-05015

Spiralwrap, 1/8" Diameter, PTFE, Natural, 100ft/RL



Download spec sheet

Base Data

Local Order Number	1P9C
Type	1P
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Sheathing allows flexible routing and lead-out of cables • The inner edges are beveled preventing damage to cables • Sheathing is reusable and resistant to most chemicals • Spiralwrap is U.L. Recognized
Product Description	HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.
Short Description	Spiralwrap, 1/8" Diameter, PTFE, Natural, 100ft/RL

Product Dimensions

Length L (Imperial)	100.0 ft
Length L (Metric)	30.48 m
Reel Length (imperial)	100.0 ft
Variant	Spiral Binding
Bundle Diameter Min. (Imperial)	0.5 "
Bundle Diameter Min. (Metric)	12.7 mm
Bundle Diameter Max. (Imperial)	0.063 "
Bundle Diameter Max. (Metric)	1.6 mm
Diameter D (imperial)	0.125 "
Diameter D (metric)	3.18 mm
Nominal Diameter (Imperial)	1/8 "
Nominal Diameter (Metric)	3.18 mm
Wall Thickness WT (Imperial)	0.020 "
Wall Thickness WT (Metric)	0.51 mm
Pitch (imperial)	0.187 "
Pitch (metric)	4.75 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	100.0 ft
Package Quantity (Metric)	30.48 m
Carton Quantity	600.0 ft

Material and Specifications

Material	Polytetrafluoroethylene -Teflon (PTFE)
Material Shortcut	PTFE
Flammability	non flammable
Operating Temperature	-449°F to +500°F (-267°C to +260°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes