

553-50019



**Article Number:** 553-50019

**Heat Shrink Label, .25" 1-Slit Single Sided, Polyolefin, White, 500/BX**



Download spec sheet

## Base Data

**Local Order Number** 553-50019

**Type** HST6-2WH-S

**Color** White (WH)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** Heat Shrink Label, .25" 1-Slit Single Sided, Polyolefin, White, 500/BX

## Product Dimensions

**Length L (Imperial)** 0.42 "

**Length L (Metric)** 10.67 mm

**Printable (Yes/No)** Yes

**Variant** Thin-Wall

**Width W (Imperial)** 0.95 "

**Width W (Metric)** 24 mm

**Height H (Imperial)** 0.42 "

**Height H (Metric)** 10.67 mm

**Diameter Max. (Imperial)** 0.25 "

**Outside Diameter Max. (Imperial)** 0.25 "

**Outside Diameter Max. (Metric)** 6.35 mm

**Wall Thickness WT (Imperial)** 0.031 "

**Wall Thickness WT (Metric)** 0.70 mm

**Print Method** Thermal Transfer

**Recovered Diameter d (metric)** 2.0 mm

**Recovered Diameter d (imperial)** 0.083 "

**Supplied Diameter D (imperial)** 0.236 "

**Supplied Diameter D (metric)** 6.0 mm

**Thickness T (Metric)** 3.0 µm

**Width of Liner WL (imperial)** 3.0 "

Width of Liner WL (metric) 76.2 mm  
Width of printable area (metric) 24.10 mm  
Width of Printable Area (imperial) 0.95 "

## Logistics and Packaging

---

Quantity Per box  
Package Quantity 500  
Package Quantity (Metric) 500  
Markers per row 2  
Weight (Metric) 0.362 kg  
Weight (imperial) 0.79 lbs

## Material and Specifications

---

Material Polyolefin, cross-linked (PO-X)  
Material Shortcut PO-X  
US MILSPEC AMS-DTL-23053/5 Class 1 and 3  
SAE-AS81531  
MIL-STD-202G Method 215K  
Dielectric Strength (Metric) 19.7 kV min.  
Flammability UL224 VW-1  
Shrink Temperature +194 °F (+90 °C)  
Operating Temperature -67°F to +275°F (-55°C to +135°C)  
ROHS Compliant Yes  
Certification/Specification UL224 125 °C 600V VW-1  
MIL-STD-202G Method 215K  
SAE-AS81531  
SAE - AMS - DTL-23053/5 Class 1 and 3