

553-50036

Article Number: 553-50036

Heat Shrink Label, .75" Unslit, Single Sided, Polyolefin, Yellow, 250/BX



Download spec sheet

## Base Data

**Local Order Number** 553-50036  
**Type** HST18-6YE  
**Color** Yellow (YE)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** Heat Shrink Label, .75" Unslit, Single Sided, Polyolefin, Yellow, 250/BX

## Product Dimensions

**Length L (Imperial)** 1.90 "  
**Length L (Metric)** 48.3 mm  
**Printable (Yes/No)** Yes  
**Variant** Thin-Wall  
**Width W (Imperial)** 1.90 "  
**Width W (Metric)** 48 mm  
**Height H (Imperial)** 1.20 "  
**Height H (Metric)** 30.48 mm  
**Diameter Max. (Imperial)** 0.75 "  
**Outside Diameter Max. (Imperial)** 0.75 "  
**Outside Diameter Max. (Metric)** 19.05 mm  
**Wall Thickness WT (Imperial)** 0.036 "  
**Wall Thickness WT (Metric)** 1.00 mm  
**Print Method** Thermal Transfer  
**Recovered Diameter d (metric)** 6.0 mm  
**Recovered Diameter d (imperial)** 0.25 "  
**Supplied Diameter D (imperial)** 0.732 "  
**Supplied Diameter D (metric)** 18.0 mm  
**Thickness T (Metric)** 3.0 µm  
**Width of Liner WL (imperial)** 3.0 "

Width of Liner WL (metric) 76.2 mm  
Width of printable area (metric) 48.26 mm  
Width of Printable Area (imperial) 1.9 "

## Logistics and Packaging

---

Quantity Per box  
Package Quantity 250  
Package Quantity (Metric) 250  
Markers per row 1  
Weight (Metric) 0.68 kg  
Weight (imperial) 1.48 lbs

## Material and Specifications

---

Material Polyolefin, cross-linked (PO-X)  
Material Shortcut PO-X  
US MILSPEC AMS-DTL-23053/5 Class 1 and 3  
SAE-AS81531  
MIL-STD-202G Method 215K  
Dielectric Strength (Metric) 19.7 kV min.  
Flammability UL224 VW-1  
Shrink Temperature +194 °F (+90 °C)  
Operating Temperature -67°F to +275°F (-55°C to +135°C)  
ROHS Compliant Yes  
Certification/Specification UL224 125 °C 600V VW-1  
MIL-STD-202G Method 215K  
SAE - AMS - DTL-23053/5 Class 1 and 3  
SAE-AS81531