

594-03000

Article Number: 594-03000

Laser Tag Label, 3.5" X .50", For Fiber Distribution Chassis, Polyester, White, 1000/pkg

HellermannTyton



Download spec sheet

Base Data

Local Order Number 594-03000

Type FDCLASER

Color White (WH)

Features and Benefits

- Laser Tags are durable, laser printable labels for applications requiring clear, crisp legibility.
- Labels come on 8.5" x 11" sheets and are printable using HellermannTyton TagPrint Pro software and a standard laser printer for easy use.
- Specially designed adhesives and materials are used for the Laser Tags, ensuring that the labels will not curl, change color, or jam laser printers.

Color Marking Field White (WH)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Short Description Laser Tag Label, 3.5" X .50", For Fiber Distribution Chassis, Polyester, White, 1000/pkg

Product Dimensions

Length L (Imperial) 0.5 "

Length L (Metric) 12.7 mm

Width W (Imperial) 3.5 "

Width W (Metric) 88.9 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Height of printable area (imperial) 3.50 "

Height of printable area (metric) 88.9 mm

Horizontal Repeat HR (metric) 88.9 mm

Horizontal Repeat HR (imperial) 3.5 "

Print Method Laser

Vertical Repeat VR (metric) 12.7 mm

Vertical Repeat VR (imperial) 0.5 "

Width of Liner WL (metric) 279.4 mm

Width of Liner WL (imperial) 11.0 "

Logistics and Packaging

Quantity Per pack

Package Quantity 1000

Package Quantity (Metric) 1000

Labels per Column 2

Labels per Row 20

Labels per Sheet 40

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Adhesive Acrylic

Adhesive Shortcut Acrylic

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes