

596-00184



**Article Number: 596-00184**

**Thermal Transfer Label, 1.0" X .5", For Use On White Insert 596-00418, PET, White, 500/RL**



Download spec sheet

## Base Data

**Local Order Number** 596-00184

**Type** NPL25X13

**Color** White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description** Thermal Transfer Label, 1.0" X .5", For Use On White Insert 596-00418, PET, White, 500/RL

## Product Dimensions

**Length L (Imperial)** 0.5 "

**Length L (Metric)** 12.7 mm

**Self adhesive (Yes/No)** Yes

**Width W (Imperial)** 1.00 "

**Width W (Metric)** 25.4 mm

**Height H (Imperial)** 0.5 "

**Height H (Metric)** 12.7 mm

**Horizontal Repeat HR (imperial)** 1 "

**Horizontal Repeat HR (metric)** 25.4 mm

**Print Method** Thermal Transfer

**Vertical Repeat VR (metric)** 15.8 mm

**Vertical Repeat VR (imperial)** 0.625 "

**Width of Liner WL (metric)** 28.57 mm

**Width of Liner WL (imperial)** 1.125 "

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 500

**Package Quantity (Metric)** 500

Labels per Column 1

Labels per Row 1

## Material and Specifications

---

**Material** Polyester (PET)

**Material Shortcut** PET

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes