

596-00202

Article Number: 596-00202

Foam Nameplate, 2.375" X 2.375" Emergency Stop label, PET, Yellow, 100/RL



Download spec sheet

## Base Data

**Local Order Number** 596-00202

**Type** NPL60X60YE

**Color** Yellow (YE)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Institute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.

**Short Description** Foam Nameplate, 2.375" X 2.375" Emergency Stop label, PET, Yellow, 100/RL

## Product Dimensions

**Length L (Imperial)** 2.375 "

**Length L (Metric)** 60.3 mm

**Self adhesive (Yes/No)** Yes

**Width W (Imperial)** 2.375 "

**Width W (Metric)** 60.3 mm

**Height H (Imperial)** 2.375 "

**Height H (Metric)** 60.3 mm

**Mounting Hole Diameter D (Imperial)** 1.20 "

**Mounting Hole Diameter D (Metric)** 30.48 mm

**Horizontal Repeat HR (metric)** 66.6 mm

**Horizontal Repeat HR (imperial)** 2.625 "

**Mounting Hole Diameter D Max.** 30.48 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 30.48 mm

**Print Method** Thermal Transfer

**Vertical Repeat VR (imperial)** 2.375 "

**Vertical Repeat VR (metric)** 60 mm

**Width of Liner WL (imperial)** 2.55 "

**Width of Liner WL (metric)** 64.77 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	100
<b>Package Quantity (Metric)</b>	100

## Material and Specifications

---

<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes