

596-00242

Article Number: 596-00242

Clear Laminate, UV stable, 4.2" X 2.25", Acrylic, Clear, 50/RL



Download spec sheet

Base Data

Local Order Number 596-00242

Type LAM1

Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4.2" X2.25" Clear acrylic UV stable laminate. This laminate can be hand applied to variable printed PV solar labels for added UV and environmental protection in outdoor conditions. 50 per roll.

Short Description Clear Laminate, UV stable, 4.2" X2.25", Acrylic, Clear, 50/RL

Product Dimensions

Width W (Imperial) 4.2 "

Width W (Metric) 106.6 mm

Height H (Imperial) 4.2 "

Height H (Metric) 57.1 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50

Package Quantity (Metric) 50

Material and Specifications

Material Acrylic (AR)

Material Shortcut AR

Adhesive Shortcut Acrylic

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)

Halogenfree Yes

Operating Temperature -20°F to +302°F (-29°C to +150°C)

ROHS Compliant Yes
Certification/Specification UL969
UL Recognized (US) Yes