

596-00243

Article Number: 596-00243

Pre-Printed Solar Label, Reflective, "MAIN PV DISCONNECT", 5.5' X 1.75", Vinyl, Red, 50/pkg

MAIN PV SYSTEM
DISCONNECT



Download spec sheet

Base Data

Local Order Number 596-00243

Type MPVSD

Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 5.5" X 1.75" White text on red background that reads as: "MAIN PV SYSTEM DISCONNECT." in 3/8" tall characters. 50 per pkg.

Local Order Number 2 Spanish Version: 596-00819

Short Description Pre-Printed Solar Label, Reflective, "MAIN PV DISCONNECT", 5.5' X 1.75", Vinyl, Red, 50/pkg

Product Dimensions

Length L (Imperial) 5.5 "

Length L (Metric) 139.7 mm

Width W (Imperial) 5.5 "

Width W (Metric) 139.7 mm

Height H (Imperial) 1.75 "

Height H (Metric) 44.4 mm

Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

Material and Specifications

Material Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

Material Shortcut 242/552

Adhesive Shortcut Acrylic

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

Certification/Specification UL969

UL Recognized (US) Yes