

596-00244

Article Number: 596-00244

Pre-Printed Solar Label, Reflective, "DO NOT DISCONNECT UNDER LOAD", 6.5" X 1.0", Vinyl, Red, 50/pkg

DO NOT DISCONNECT  
UNDER LOAD



Download spec sheet

## Base Data

Local Order Number 596-00244

Type DNDCUL

Color Red (RD)

**Features and Benefits**

- Made with UV stable inks and materials for durability and weather resistance
- Supplied with aggressive adhesive to ensure long life
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
- Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 6.5" X 1" White text on red background that reads as: "DO NOT DISCONNECT UNDER LOAD" in 3/8" tall characters. 50 per pkg.

Local Order Number 2 Spanish Version: 596-00820

**Short Description** Pre-Printed Solar Label, Reflective, "DO NOT DISCONNECT UNDER LOAD", 6.5" X 1.0", Vinyl, Red, 50/pkg

## Product Dimensions

Length L (Imperial) 6.5 "

Length L (Metric) 165.1 mm

Width W (Imperial) 6.5 "

Width W (Metric) 165.1 mm

Height H (Imperial) 1.0 "

Height H (Metric) 25.4 mm

## Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

## Material and Specifications

Material Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

**Material Shortcut** 242/552

**Adhesive Shortcut** Acrylic

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +174°F (-40°C to +79°C)

**ROHS Compliant** Yes

**Certification/Specification** UL969

**UL Recognized (US)** Yes