

596-00251



Article Number: 596-00251

Pre-Printed Solar Marker, Reflective, Non-Adhesive, Coiled, "CAUTION: SOLAR CIRCUIT", 7.25" X 5", Vinyl, Red, 25/pkg



Download spec sheet

Base Data

Local Order Number 596-00251

Type CSCSNAP72R

Color Red (RD)

- Features and Benefits**
- Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.
 - Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.
 - Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.
 - The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 7.2" X 5" White text with red background that reads as:
"CAUTION - SOLAR CIRCUIT" in 3/8" tall characters using reflective inks. 25/PKG

Short Description Pre-Printed Solar Marker, Reflective, Non-Adhesive, Coiled, "CAUTION: SOLAR CIRCUIT", 7.25" X 5", Vinyl, Red, 25/pkg

Product Dimensions

Width W (Imperial) 7.25 "

Width W (Metric) 127.0 mm

Height H (Imperial) 5.0 "

Height H (Metric) 127.0 mm

Horizontal Repeat HR (imperial) 7.2 "

Horizontal Repeat HR (metric) 182.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 25

Package Quantity (Metric) 25

Material and Specifications

Material Vinyl

Material Shortcut VL

Halogenfree Yes

Operating Temperature -18°F to +200°F (-29°C to +93°C)

ROHS Compliant Yes