HellermannTyton

596-00258

WARNING LTAIC SYSTEM ARE UNGROUNDED Article Number: 596-00258

Pre-Printed Solar Label, "WARNING - DC CONDUCTORS MAY BE...", 4.12" X 2", Vinyl,Red, 50/RL





Base Data

Local Order Number 596-00258

Type WDCCU

Color Red (RD)

- Features and Benefits Made with UV stable inks and materials for durability and weather resistance.
 - The labels are supplied with aggresive adhesive to ensure long life.
 - · Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability

to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptalbe to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4.12" X2" White text on red background that reads as:

"WARNING - ELECTRICAL SHOCK HAZARD. THE DC CONDUCTORS OF THIS PHOTOVOLTAIC SYSTEM ARE

UNGROUNDED AND MAY BE ENERGIZED" - 50 per roll.

Short Description Pre-Printed Solar Label, "WARNING - DC CONDUCTORS MAY BE...", 4.12" X2", Vinyl, Red, 50/RL

Product Dimensions

Width W (Imperial) 4.12 "

Width W (Metric) 104.6 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity (Metric) 50

Material and Specifications

Material Type 443/552, UV Stable Flexible White Vinyl w/Acryclic Laminate

Material Shortcut 443/552

Adhesive Shortcut Acrylic

Adhesive Acrylic

Halogenfree Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

Certification/Specification UL969

UL Recognized (US) Yes

© HellermannTyton 2015