

596-00406

Article Number: 596-00406

Foam Nameplate, 1.2" X 1.5" Button Label With .88" Hole, PET, Red, 250/RL



Download spec sheet

Base Data

Local Order Number 596-00406

Type NPLH31X38RD22.5

Color Red (RD)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
 - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
 - Labels are UV and chemical resistant for long life in an industrial environment.
 - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

Product Description Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

Short Description Foam Nameplate, 1.2" X 1.5" Button Label With .88" Hole, PET, Red, 250/RL

Product Dimensions

Length L (Imperial) 1.5 "

Length L (Metric) 38.1 mm

Self adhesive (Yes/No) Yes

Width W (Imperial) 1.2 "

Width W (Metric) 30.5 mm

Height H (Imperial) 1.5 "

Height H (Metric) 38.1 mm

Mounting Hole Diameter D (Imperial) 0.88 "

Mounting Hole Diameter D (Metric) 22.35 mm

Horizontal Repeat HR (imperial) 1.2 "

Horizontal Repeat HR (metric) 30.5 mm

Mounting Hole Diameter D Max. 22.35 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 22.35 mm

Print Method Thermal Transfer

Vertical Repeat VR (metric) 41.27 mm

Vertical Repeat VR (imperial) 1.625 "

Width of Liner WL (imperial) 1.45 "

Width of Liner WL (metric) 36.83 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	250
Package Quantity (Metric)	250
Labels per Column	1
Labels per Row	1

Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Operating Temperature	-40°F to +176°F (-40°C to +80°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes