

596-00412



**Article Number:** 596-00412

**Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, White, 250/RL**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 596-00412

**Type** NPLH31X31WH22.5

**Color** White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description** Foam Nameplate, 1.25" X 1.25" Button Label With .88" Hole, PET, White, 250/RL

## Product Dimensions

**Length L (Imperial)** 1.25 "

**Length L (Metric)** 31.7 mm

**Self adhesive (Yes/No)** Yes

**Width W (Imperial)** 1.25 "

**Width W (Metric)** 31.7 mm

**Height H (Imperial)** 1.25 "

**Height H (Metric)** 31.7 mm

**Mounting Hole Diameter D (Imperial)** 0.88 "

**Mounting Hole Diameter D (Metric)** 22.35 mm

**Horizontal Repeat HR (metric)** 31.7 mm

**Horizontal Repeat HR (imperial)** 1.25 "

**Mounting Hole Diameter D Max.** 22.35 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 22.35 mm

**Print Method** Thermal Transfer

**Vertical Repeat VR (metric)** 34.92 mm

**Vertical Repeat VR (imperial)** 1.375 "

**Width of Liner WL (imperial)** 1.5 "

**Width of Liner WL (metric)** 38.1 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (imperial)</b>	0.5 lbs
<b>Weight (Metric)</b>	0.22 kg

## Material and Specifications

---

<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes