# HellermannTyton

### 596-00651

Article Number: 596-00651

Printable Solar Label, PV DC DISCONNECT LABEL, 1.0" X 3.75", Polyester, Red, 50/RL



RoHS



## Base Data

Base Bala	
Local Order Number	596-00651
Туре	DCDISC-1
Color	Red (RD)
Features and Benefits	<ul> <li>Made with UV stable inks and materials for durability and weather resistance.</li> <li>The labels are supplied with aggresive adhesive to ensure long life.</li> <li>Solar Installation labels meet NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	1.0" X3.75" White text on red background that reads as: "PHOTOVOLTAIC DC DISCONNECT." - 50 per roll. Label is also printable with variable information by the installer. Dispensed narrow end first for use in the TT130SMC printer.
Short Description	Printable Solar Label, PV DC DISCONNECT LABEL, 1.0" X3.75", Polyester, Red, 50/RL

#### **Product Dimensions**

Width W (Imperial)	1.0 "
Width W (Metric)	25.4 mm
Height H (Imperial)	3.75 "
Height H (Metric)	95.25 mm

#### Logistics and Packaging

Quantity Per	reel
Package Quantity	50
Package Quantity (Metric)	50

#### **Material and Specifications**

Material	Polyester
Material Shortcut	PET
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
Halogenfree	Yes

Operating Temperature-40°F to +174°F (-40°C to +79°C)ROHS CompliantYesCertification/SpecificationUL969UL Recognized (US)Yes

© HellermannTyton 2015