

596-00652

Article Number: 596-00652

Printable Solar Label, PV AC RATING LABEL, 1.0" X 3.75", Polyester, Red, 50/RL



Download spec sheet

Base Data

Local Order Number	596-00652
Type	PVACDIS-1
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance.• The labels are supplied with aggressive adhesive to ensure long life.• Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	1.0" X3.75" White text on red background that reads as: "PHOTOVOLTAIC AC DISCONNECT. MAXIMUM AC OPERATING CURRENT. NOMINAL OPERATING AC VOLTAGE." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand. Dispensed narrow end first for use with the TT130SMC printer.
Short Description	Printable Solar Label, PV AC RATING LABEL, 1.0" X3.75", Polyester, Red, 50/RL

Product Dimensions

Width W (Imperial)	1.0 "
Width W (Metric)	25.4 mm
Height H (Imperial)	3.75 "
Height H (Metric)	92.25 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	50
Package Quantity (Metric)	50

Material and Specifications

Material	Polyester
Material Shortcut	PET
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
Halogenfree	Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

Certification/Specification UL969

UL Recognized (US) Yes