

596-00660



Article Number: 596-00660

Solar Label, Warning- Electrical Shock Hazard Label, 3.75" X 2.0", Vinyl, Orange/White, 10/pkg



Download drawing

Download spec sheet

Base Data

Local Order Number	596-00660
Type	WESHLBL10
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance• Supplied with aggressive adhesive to ensure long life• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	3.75" X2" Black text on an Orange/White background that reads as: "WARNING - ELECTRICAL SHOCK HAZARD. DO NOT TOUCH TERMINALS. TERMINALS ON BOTH LINE AND LOAD SIDE MAY BE ENERGIZED IN THE OPEN POSITION." - 10 per pkg.
Short Description	Solar Label, Warning- Electrical Shock Hazard Label, 3.75" X2.0", Vinyl, Orange/White, 10/pkg

Product Dimensions

Width W (Imperial)	3.75 "
Width W (Metric)	92.25 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	10
Package Quantity (Metric)	10

Material and Specifications

Material	Vinyl
Material Shortcut	VL
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Halogenfree	Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

UL Recognized (US) Yes