

596-00663



Article Number: 596-00663

Solar Label, Warning- Grounded Conductors Energized Label, 4.12" X 2.0", Vinyl, Orange/White, 10/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 596-00663
Type WGCME10
Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4.12" X2" Black text on an Orange/White background that reads as:
 "WARNING - ELECTRICAL SHOCK HAZARD. IF GROUND FAULT IS INDICATED, NORMALLY GROUNDED CONDUCTORS MAY BE UNGROUNDED AND ENERGIZED" - 10 per pkg.

Short Description Solar Label, Warning- Grounded Conductors Energized Label, 4.12" X2.0", Vinyl, Orange/White, 10/pkg

Product Dimensions

Width W (Imperial) 4.12 "
Width W (Metric) 104.6 mm
Height H (Imperial) 2.0 "
Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per pack
Package Quantity 10
Package Quantity (Metric) 10

Material and Specifications

Material Vinyl
Material Shortcut VL
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)
Halogenfree Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

UL Recognized (US) Yes