


596-00793

Article Number: 596-00793

Peel-Off Paint Shield, UV stable, 3.5" X 1.75", Polyester, Clear, 10/PK



Base Data

Local Order Number 596-00793

Type PAINTSHIELD2

Color Clear (CL)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
 - Supplied with aggressive adhesive to ensure long life
 - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
 - Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 3.5" X 1.75" Peel-off paint shield, UV Stable Clear Polyester, for use with 596-00828, 596-00830, 596-00831, 596-00832, 596-00837, 596-00835, 596-00497, 596-00590, 596-00591

Short Description Peel-Off Paint Shield, UV stable, 3.5" X 1.75", Polyester, Clear, 10/PK

Product Dimensions

Width W (Imperial) 3.5 "

Width W (Metric) 88.9 mm

Height H (Imperial) 1.75 "

Height H (Metric) 44.45 mm

Logistics and Packaging

Quantity Per pack

Package Quantity (Metric) 10

Material and Specifications

Material Type 240, 2.0 Mil Polyester (PET), Clear (CL)

Material Shortcut 240

Adhesive Shortcut Acrylic

Adhesive 1.0 Mil Aggressive Removable

Adhesive Operating Temperature from +50°F (from +10°C)

Halogenfree Yes

Operating Temperature -20°F to +302°F (-29°C to +150°C)

ROHS Compliant Yes

