

596-00802

Article Number: 596-00802



Pre-Printed Solar Label, Spanish Version, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X 2.5", Vinyl, Orange/White, 50/RL



Download spec sheet

Base Data

Local Order Number 596-00802

Type WESHLBLDCS

Color Orange (OG)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
 - Supplied with an aggressive adhesive to ensure long life
 - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
 - Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 3.75" X2.5" Black text on an Orange/White background that reads as: "WARNING - ELECTRICAL SHOCK HAZARD. DO NOT TOUCH TERMINALS. TERMINALS ON BOTH LINE AND LOAD SIDE MAY BE ENERGIZED IN THE OPEN POSITION. DC VOLTAGE IS ALWAYS PRESENT WHEN SOLAR MODULES ARE EXPOSED TO SUNLIGHT" - 50 per roll

Local Order Number 2 English Version: 596-00496

Short Description Pre-Printed Solar Label, Spanish Version, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X2.5", Vinyl, Orange/White, 50/RL

Product Dimensions

Length L (Imperial) 3.75 "

Length L (Metric) 95.25 mm

Width W (Imperial) 3.75 "

Width W (Metric) 95.25 mm

Height H (Imperial) 2.5 "

Height H (Metric) 63.5 mm

Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

Material and Specifications

Material	Type 443/552, UV Stable Flexible White Vinyl w/Acrylic Laminate
Material Shortcut	443/552
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Halogenfree	Yes
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
ROHS Compliant	Yes
Certification/Specification	UL969
UL Recognized (US)	Yes