

596-00808

Article Number: 596-00808

Pre-Printed Solar Label, Spanish Version, "WARNING - BIPOLAR PV ARRAY", 3.75" X 2", Vinyl, Orange/White, 50/RL



Download spec sheet

Base Data

Local Order Number 596-00808

Type CBACKFEDS

Color Orange (OG)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
 - Supplied with an aggressive adhesive to ensure long life
 - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
 - Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 3.75" X2" Black text on an Orange/White background that reads as: "WARNING - BIPOLAR PHOTOVOLTAIC ARRAY. DISCONNECTION OF NEUTRAL OR GROUNDED CONDUCTORS MAY RESULT IN OVERVOLTAGE ON ARRAY OR INVERTER." - 50 per roll.

Local Order Number 2 English Version: 596-00590

Short Description Pre-Printed Solar Label, Spanish Version, "WARNING - BIPOLAR PV ARRAY", 3.75" X2", Vinyl, Orange/White, 50/RL

Product Dimensions

Length L (Imperial) 3.75 "

Length L (Metric) 95.25 mm

Width W (Imperial) 3.75 "

Width W (Metric) 95.25 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

Material and Specifications

Material Type 443/552, UV Stable Flexible White Vinyl w/Acryclic Laminate
Material Shortcut 443/552
Adhesive Acrylic
Adhesive Shortcut Acrylic
Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)
Halogenfree Yes
Operating Temperature -40°F to +174°F (-40°C to +79°C)
ROHS Compliant Yes
Certification/Specification UL969
UL Recognized (US) Yes