

596-00810

Article Number: 596-00810

Pre-Printed Solar Label, Reflective, Spanish Version, "SOLAR DISCONNECT", 6.5" X 1", Vinyl, Red, 50/pkg

DESCONECTADOR SOLAR



Download spec sheet

Base Data

Local Order Number 596-00810

Type SOLARDS

Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance
- Reflective properties to meet applicable NEC code requirements for reflective identification.
- Supplied with an aggressive adhesive to ensure long life
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 6.5" X 1" White text on a red background that reads as: "SOLAR DISCONNECT" in 3/8" tall characters using reflective inks. 50 per pkg.

Local Order Number 2 English Version: 596-00246

Short Description Pre-Printed Solar Label, Reflective, Spanish Version, "SOLAR DISCONNECT", 6.5" X 1", Vinyl, Red, 50/pkg

Product Dimensions

Length L (Imperial) 6.5 "

Length L (Metric) 165.1 mm

Width W (Imperial) 6.5 "

Width W (Metric) 165.1 mm

Height H (Imperial) 1.0 "

Height H (Metric) 25.4 mm

Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

Material and Specifications

Material Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

Material Shortcut 242/552

Adhesive Acrylic

Adhesive Shortcut Acrylic

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes

Operating Temperature -40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

UL Recognized (US) Yes