

596-00817

Article Number: 596-00817

Printable Solar Label, Spanish Version, DC Module Label, 4.0" X 2.0", Polyester, Red, 50/RL



Download spec sheet

## Base Data

Local Order Number 596-00817

Type DC2011S

Color Red (RD)

**Features and Benefits**

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 4" X2" White text on red background that reads as: "RATED MAX POWER-POINT CURRENT;RATED MAX POWER-POINT CURRENT;MAXIMUM SYSTEM VOLTAGE;MAXIMUM CIRCUIT CURRENT;MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER (IF INSTALLED." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Local Order Number 2 English Version: 596-00253

Short Description Printable Solar Label, Spanish Version, DC Module Label, 4.0" X2.0", Polyester, Red, 50/RL

## Product Dimensions

Length L (Imperial) 4.0 "

Length L (Metric) 101.6 mm

Width W (Imperial) 4.0 "

Width W (Metric) 101.6 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

## Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

## Material and Specifications

Material Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

**Material Shortcut** 840/926

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +180°F (-40°C to +82°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes

**Certification/Specification** UL969

**UL Recognized (US)** Yes