

596-00824

Article Number: 596-00824

Pre-Printed Solar Label, Spanish Version, "WARNING - 120-VOLT SUPPLY", 3.75" X 2", Vinyl, Orange/White, 50/RL



Download spec sheet

## Base Data

**Local Order Number** 596-00824

**Type** 120VOLTS

**Color** Orange (OG)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
  - Supplied with an aggressive adhesive to ensure long life
  - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
  - Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 3.75" X2" Black text on an Orange/White background that reads as: "WARNING - SINGLE 120-VOLT SUPPLY DO NOT CONNECT MULTIWIRE BRANCH CIRCUITS" - 50 per roll.

**Local Order Number 2** English Version: 596-00591

**Short Description** Pre-Printed Solar Label, Spanish Version, "WARNING - 120-VOLT SUPPLY", 3.75" X2", Vinyl, Orange/White, 50/RL

## Product Dimensions

**Length L (Imperial)** 3.75 "

**Length L (Metric)** 95.25 mm

**Width W (Imperial)** 3.75 "

**Width W (Metric)** 95.25 mm

**Height H (Imperial)** 2.0 "

**Height H (Metric)** 50.8 mm

## Logistics and Packaging

**Quantity Per** roll

**Package Quantity** 50

**Package Quantity (Metric)** 50

**Labels per Column** 1

**Labels per Row** 1

## Material and Specifications

**Material** Type 443/552, UV Stable Flexible White Vinyl w/Acryclic Laminate

**Material Shortcut** 443/552

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +174°F (-40°C to +79°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +174°F (-40°C to +79°C)

**ROHS Compliant** Yes

**Certification/Specification** UL969

**UL Recognized (US)** Yes